

**Efficiently Moving Grain** 



- Easy transport without the need to change wheel position.
- New chassis and towbar design.
- Extra short, 8-mm thick, heavily reinforced horizontal auger.

Reduces grain damage

- Removable sleeve
- High-capacity reception hopper
- High-strength structure built with shaped tubes and stamped sheets.
- Chain drive with automatic tensioner.
- Towbar hydraulic height adjustment.
- Brake panel (Left or right side, optional)
- Support leg to release the tractor.
- Work or running lights (optional).
- Rubber flap that prevents grain spill.

## **Great Capacity!!! 900 ton/hour!!!** the simplest and fastest way to load bags!

## Easy Lift system.

- For bags up to 100 meters long.
- Less power consumption
- Minimum tunnel and operating height (chassis/ground)
- Transport stability and uniform bag filling.
- Bag loading is easier than ever.
- It minimizes the required number of operators.

TECHNICAL SPECIFICATIONS	
Tunnel for bags of (feet)	9
Auger tube diameter (mm)	500
Hopper Capacity (liters)	1,850
Power Required (HP)	65
Brake System	Hydraulic
Pan	Hydraulic
Easy Lift system*	Hydraulic / Manual
Tires	8.25 x 16









Rosario de Santa Fe 2256 X2400EFN San Francisco CBA, Argentina Tel/Fax: + 54 3564 498502 export@akron.com.ar

www.akronag.com

**AKRON** may change specifications and product designs in this or other brochure at any time, without previous notice. Pictures shown are for illustration purposes only.

