


**Efficiently Moving Grain** 





- Modern design: simple versatile operation.
- **Heavily reinforced chassis:** allows an easier unloading operation.
- Bottom angular gearbox and grain pusher: simplify the auger's performance and ensure a better end of bag.
- Independent hydraulic controls.
- **Hydrostatic movement:** The machine moves automatically as the bag is wound up by the roller. The speed of movement can be adjusted.
- Single operating and transport position.
- **Tires:** 235/70 15".
- Electrostatic polyurethane paint.





## **Great Capacity!!! 360 tonnes/hour**

## It fully winds up the grain bag. Automatic movement independent of the tractor traction.

For bags of	9 feet	
Unloading performance	13,230 bu/hour	
Power required	75 HP	
Tube/Auger diameter	15 <sup>3</sup> / <sub>4</sub> in	
Horizontal Auger diameter	10 <sup>1</sup> / <sub>4</sub> in	

**EX3600** 





Rosario de Santa Fe 2256 X2400EFN Sán Francisco CBA, Argentina Tel/Fax: + 54 3564 498502 export@akron.com.ar

www.akronag.com

AKRON may change specifications and product designs in this or other brochure at any time, without previous notice. Pictures shown are for illustration purposes only.









Height adjustment through hydraulic cylinder.

Grain Pusher. It ensures a better end of bag.

Independent hydraulic controls.

Speed Control Valve.

Bag Deflectors.